


Under Shelf Light



L/C

LIGHTCORP



FEATURES:

- Modular design

SPECIFICATIONS:

ENERGY CONSUMPTION	see chart below
NUMBER OF LEDS	see chart below
LIGHT OUTPUT	see chart below
LED RATED LIFESPAN	> 60,000 hours
COLOR TEMPERATURE	3500K
COLOR RENDERING INDEX	83
POWER SUPPLY	18-watt wall transformer with 9' black cord
MATERIALITY	plastic
CERTIFICATIONS	ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA
WARRANTY	5 years

	# LEDS	LUMENS	WATTAGE	SYSTEM WATTAGE
12" fixture	12	324	5.0	5.1
22" fixture	24	639	9.0	9.8
32" fixture	36	951	12.0	14.12
42" fixture	48	1244	16.0	18.15

DIMENSIONS:

	W	H	D
12" fixture	11.1"	.71"	.85"
22" fixture	21.2"	.71"	.85"
32" fixture	31.2"	.71"	.85"
42" fixture	41.3"	.71"	.85"

SUSTAINABILITY NOTES:

- Made with fully-recyclable plastic. Please contact your local county or municipality to determine your local recycling options.
- Lower power consumption
- Mercury-free
- Potential LEED points. For more LEED information please visit <https://new.usgbc.org/leed-v4l>

MOUNTING:

Mounting magnets and keyhole slots are integrated into the fixture for most mounting applications.

FINISH:

SILVER

PHOTOMETRIC DATA:

Footcandle outputs measured at 18" from the work surface.

12" Fixture	18"	12"	6"	CL	6"	12"	18"
12"	8	14	20	23	20	14	8
6"	11	21	36	43	36	21	11
CL	12	26	44	54	44	26	12
6"	11	21	36	43	36	21	11
12"	8	14	20	23	20	14	8

22" Fixture	18"	12"	6"	CL	6"	12"	18"
12"	20	31	39	42	39	31	20
6"	32	52	69	75	69	52	32
CL	38	65	87	94	87	65	38
6"	32	52	69	75	69	52	32
12"	20	31	39	42	39	31	20

32" Fixture	18"	12"	6"	CL	6"	12"	18"
12"	35	45	50	52	50	45	35
6"	58	76	85	87	85	76	58
CL	72	94	105	108	105	94	72
6"	58	76	85	87	85	76	58
12"	35	45	50	52	50	45	35

42" Fixture	18"	12"	6"	CL	6"	12"	18"
12"	49	55	58	58	58	55	49
6"	83	91	95	96	95	91	83
CL	102	113	117	118	117	113	102
6"	83	91	95	96	95	91	83
12"	49	55	58	58	58	55	49

SPECIFICATION NOTES:

- Each fixture includes one end cap to enclose the open end of the fixture, 2 adhesive cord managers and mounting screws.
- Maximum 4 modular segments connected per 18-watt power supply.
- Individual adder unit does not include end cap.
- Individual adder units cannot be added to the 42" fixture.
- White power supply and cord available upon request by calling Inside Sales at 800.526.5658.
- Additional cord managers are available for purchase.
- Do not interlink with any other fixture family.