





Magnifier

Epic® LED Magnifier

The perfect combination of light quality, positionability and large viewing area.

Burton's Epic LED Magnifier has an arm and neck system that is rugged and flexible. It stays exactly where it's positioned and doesn't require tightening or lock mechanism adjustments.

Features

- · Large optical viewing area
- Superb light quality; 90 CRI, 4000 Kelvin
- 10-100% dimming capability
- Auto shut-off
- Smooth surface, easy to clean, anti-microbial coating
- Low maintenance LED array
- Medical standards approved
- Available in Floor Stand and Wall/Table Models
- 5-year limited warranty







19.7"

Ordering Information **EPIC LED MAGNIFIER**

EPIC LED MAGNIFIER

Universal Input 100-240v	
50/60Hz Model	Description
EMLFL	Epic LED Magnifier, Floor Stand, NEMA 5-I5P
EMLT	Epic LED Magnifier, Table Mount, NEMA 5-I5P
EMLW	Epic LED Magnifier, Wall Mount, NEMA 5-15P
EMLFL01	Epic LED Magnifier, Floor Stand, CEE 7/7
EMLFL02	Epic LED Magnifier, Floor Stand, AS/NZS 3112
EMLFL03	Epic LED Magnifier, Floor Stand, BSI363
EMLT01	Epic LED Magnifier, Table Mount, CEE 7/7
EMLT02	Epic LED Magnifier, Table Mount, AS/NZS 3112
EMLT03	Epic LED Magnifier, Table Mount, BSI363
EMLW01	Epic LED Magnifier, Wall Mount, CEE 7/7
EMLW02	Epic LED Magnifier, Wall Mount, AS/NZS 3112
EMLW03	Epic LED Magnifier, Wall Mount, BSI363

Magnification Table

Primary Lens Diopter	Secondary Lens Diopter (optional)	Total Magnification	Total Diopter	Magnification %	Focal Length (in.)
3.5		1.88X	3.5	188%	П
3.5	4.0	2.88X	7.5	288%	5
3.5	6.0	3.38X	9.5	338%	4
3.5	10.0	4.38X	13.5	438%	3

Summary of technical data

EPIC LED MAGNIFIER

Optics:	3.5 Diopter (1.88X magnification)
Viewing Area Diameter:	6.5" (16.5 cm)
Illuminance:	1,360 Lux (126 fc) at 8" (20 cm) 3,830 Lux (356 fc) at 11" (28 cm)
Color Temperature:	4000 Kelvin
CRI (Color Rendering Index):	90
Light Source:	Light Emmitting Diode (LED)
Rated Life of LED	50,000-hour average rated LED life
Power:	10 Watts
Mounting Options:	Mobile Floor Stand, Wall/Table Mount
Maximum Arm Reach:	39" (99 cm)
Applications:	General examination
Certifications/Approvals:	IEC 60601-1 (SAFETY) / EC 60601-1-2, (EMC) / IEC
Cerunicacions/Approvais.	60601-2-41 / IEC 60601-1-6 / CAN/CSA-22.2 60601-1:14
Product Warranty:	5-year limited warranty

ACCESSORIES

Model	Description
EML4DS	4 Diopter Lens Attachment
EML6DS	6 Diopter Lens Attachment
EML10DS	10 Diopter Lens Attachment
IFC Plug Type	

IEC Plug Type









Default (No Code): NEMA 5-15P 01: CEE 7/7

02: AS/NZS 3112

03: B51363

Add appropriate Plug Type to the end of the model number.



Example 1: EMLFL for a 100-240v Floor Stand Model with Nema 5-15P Plug.

Example 2: EMLFL01 for a 100-240v Floor Stand Model with SCHUKO CEE 7/7 to C60320C13Plug.

¹100-120v Do not add Plug Type, NO CODE: NEMA 5-15P, 01: CEE 7/7, 02:AS/NZS 3112, 03: BS1363.





© 2018 Burton Medical. All rights reserved. Burton Medical reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.



Burton Medical, LLC 2300 W Windsor Ct., Suite C Addison, IL 60101 USA Phone (800) 444-9909, Fax (800) 765-1770 Burtonmedical.com